NEWTEC WEIGHING MACHINE MD-SERIES

**\_**:::

WEIGHING MACHINES

h3009MD / h3013MD

WIDTH OF WEIGH HEADS 89 MM HEIGHT OF WEIGH HEADS 195 MM

ALSO AVAILABLE FOR CHERRIES



Model h3013MD

# Gentle high speed weigher - for fragile products

#### Advantages

- Small machine with gentle product handling and low drops
- Combining speed and weighing accuracy
- High speed up to 90 portions/min.at 0,5 kg (h3013MD)
- High weighing accuracy: Typical giveaway: less than 0.4%
- Robustly constructed in stainless steel
- Vibrator chutes for optimal distribution of products to the weigh heads
- Option: Newtec WebServices for remote servicing, data collection and analysis
- Option: Newtec MachineLink for easy control of more Newtec machines from only one touchscreen

NEWTE

#### Application

Washed vegetables and fruits such as:

- Tomatoes Cherry tomatoes Small potatoes Nectarines Clementines Kiwi
- Plums Nuts Brussel Sprouts Leeks Peppers and similar products
- Cherries (cherry kit)



WEBSERVICES AVAILABLE FOR REMOTE SERVICING

# WEIGHING MACHINE h3009MD / h3013MD

## **NEWTEC**

and a start of the

#### YOUR ADVANTAGES

- User friendly software - programmable in seconds
- Count by weight, minimum weight or average weight programs
- Capable of running with one or more channels disabled
- Small V-shaped weigh heads with double opening for gentle handling of products
- Small footprint and low cost of ownership
- Option: "top pan tilt" for easy and quick access for cleaning and service


Model h3009MD Option: Cherry brush

> Option: Top pan tilt



## FOR CHERRIES


• Round cherry brush for optimal handling of double cherries



NEWTEC

NEWTEC

#### 3013MD: 1792 3009MD: 1340 БЦ



#### NEWTEC SOFTWARE

- Intuitive user interface
- Informative and upgradable
- Same user interface on all Newtec weighing and packing machines



#### WEIGHING MACHINE WITH 9 / 13 CHANNELS

Model	h3009MD	h3013MD
Speed / Capacity	Up to 50 portions/ min. at 0,50 kg.	Up to 90 portions/ min. at 0,50 kg.
Weight	450 kg. (excl. portion collection system)	480 kg. (excl. portion collection system)

Portions sizes	0,25-1,0 kg (depending on product)
Air requirement Connection Min. pressure Consumption	3/8" 6 bar (0.6 Mpa) 250 NL/min.
Weigh head volume Weigh head width	2,0 L 89 mm
Material	According to the EU/FDA rules on food contact materials
Protection class	IP54
Electrical requirement	3x220 VAC or 3x400 VAC (N)+PE
Environment	5° C – 35° C

newtec.com