NEWTEC WEIGHING MACHINE PC-SERIES

2009PC / 2014PC

WIDTH OF WEIGH HEADS 102 MM HEIGHT OF WEIGH HEADS 208 MM



Accurate combination weighing of processed food

Advantages

- Combining speed and weighing accuracy
- High weighing accuracy: Typical giveaway: less than 0.4%
- High speed up to 100 portions/min. at 0,25 kg (2014PC)
- Vibrator chutes for optimal distribution of products to the weigh heads
- Detachable weigh heads for easy cleaning
- Rigidised stainless steel on all surfaces with food contact to minimize bridging of products
- Option: Newtec WebServices for remote servicing, data collection and analysis
- Option: Newtec MachineLink for easy control of more Newtec machines from only one touchscreen

Application

Processed food such as:

- Fresh and frozen products Fish fillets Squids Shellfish Broccoli
- Brussel Sprouts Bell Peppers Cherries Nuts Potato Chips
- Similar fresh and frozen products




WEBSERVICES AVAILABLE FOR REMOTE SERVICING

WEIGHING MACHINE 2009PC / 2014PC

NEWTEC

YOUR ADVANTAGES

- User friendly software
 programmable in seconds
- Count by weight, minimum weight or average weight programs
- Capable of running with one or more channels disabled
- Removable weigh heads – no tools required
- Easy access for cleaning and service
- Low friction surfaces



RIGIDISED STAINLESS STEEL

Air requirement Connection

Min. pressure

Consumption

Weigh head volume

Weigh head width

Protection class

Material

Electrical

requirement

Environment

COMBINATION WEIGHING MACHINE WITH 9 / 14 CHANNELS

Model	2009PC	2014PC
Speed / Capacity	Up to 60 portions/ min. at 0,25 kg.	Up to 100 portions/ min. at 0,25 kg.
Weight	350 kg. (excl. portion collection system)	490 kg. (excl. portion collection system)
Portions sizes	0,25 - 1 kg. (depending on product)	0,25 - 2 kg. (depending on product)

3/8"

2,3 L

IP65

102 mm


6 bar (0.6 Mpa)


25-50 NL/min.

3x220 VAC or

3x400 VAC (N)+PE


According to the EU/FDA rules on food contact materials





Width: 102 mmDepth: 147 mm

• Theoretical volume: 2,3 L



NEWTEC SOFTWARE

- Intuitive user interface
- Informative and upgradable
- Same user interface on all Newtec weighing and packing machines



5° C – 40° C

newtec.com